

EN3 Water & Foam Type Fire Extinguisher

PRESSURE EQUIPMENT DIRECTIVE
APPROVED FIRE EXTINGUISHERS



0029

MARINE EQUIPMENT DIRECTIVE
APPROVED FIRE EXTINGUISHERS



0029



BRITISH STANDARDS INSTITUTION



CERTIFIED TO BS EN3
LICENCE NO. KM 57533



SETSCO



- EN3 approved.
- Foam type is suitable for Class A & B.
- Water type is suitable for Class A.
- Protective plastic lining.
- Colour coded for instant recognition.
- High quality and good value.

TECHNICAL SPECIFICATION

EXTINGUISHER TYPE	6L FOAM	2L FOAM*	9L FOAM	9L WATER	9L FOAM	9L WATER
	STORE PRESSURE TYPE (NITROGEN PROPELLENT)			CO2 CARTRIDGE		
MODEL NO.	FEX102	FEX116	FEX103	FEX101	FEX112	FEX111
FIRE RATING	13A, 144B	5A, 34B	21A, 183B	13A	13A, 183B	13A
OPERATING TEMPERATURE	5°C to 60°C					
OPERATING PRESSURE	12 Bar					
TEST PRESSURE	25 Bar					
HEIGHT	555mm	400mm	625mm	625mm	630mm	630mm
FULL WEIGHT	9.2kg	4.0kg	13.5kg	13.5kg	14.2kg	14.2kg
DISCHARGE TIME	33-38 secs	10-14 secs	44-49 secs	61-65 secs	93-97 secs	88-92 secs
RANGE OF THROW (approx)	4 - 5 M	2 M	4 - 5 M	6 M	4 - 5 M	6 M
CARTON SIZE mm	190 x 210 x 565	125 x 160 x 430	200 x 200 x 646	200 x 200 x 645	200 x 200 x 645	200 x 200 x 645

*Certification in progress

The products specified in this brochure are subjected to continuous development and improvement and are subject to alterations without prior notice. All dimensions are in mm unless otherwise specified.