

BRANCHPIPE NOZZLES



JET NOZZLE COMPLETE WITH BRANCHPIPE

Code No.	Material	Finishing	Inlet Size	Flowrate @ 65Psi (4.4 Bar)	Throwrange @ 65Psi (4.4 Bar)
WRS077-LA-STD-NA WRS077-GM-STD-NA	Aluminium Alloy	Natural	Male Instantaneous BS 336	210L/min (12mm dia.)	16m (12mm dia.)
	to BS 1490 Copper Alloy to BS 1982			510L/min (19mm dia.)	22m (19mm dia.)

This nozzle is available with two orifice sizes, 12mm and 19mm. Application: Hydrant system, wet or dry riser system



DIFFUSER NOZZLE 500 (JET/SPRAY)

Code No.	Туре	Material	Finishing	Inlet Size	Flowrate @ 65Psi (4.4 Bar)	Throwrange @ 65Psi (4.4 Bar)
WRS099-LA-STD-NA	Standard	Aluminium Alloy		Male		,
WRS101-LA-STD-NA	With branchpipe	to BS 1490	Natural	Instantaneous	500L/min (JET)	26m (JET)
WRS099-GM-STD-NA	Standard	Copper Alloy to BS 1982		BS 336	590L/min (SPRAY)	15m (SPRAY)
WRS101-GM-STD-NA	With branchpipe				(2)	(27 (41))
WRS106-GM-52C-NA	Storz inlet			Storz DIN 52C		



DIFFUSER NOZZLE 800 (JET/SPRAY)

Code No.	Туре	Material	Finishing	Inlet Size	Flowrate @ 65Psi (4.4 Bar)	Throwrange @ 65Psi (4.4 Bar)
WRS100-LA-065-NA	Standard	Aluminium Alloy to BS 1490	Natural	Male Instantaneous BS 336	800L/min (JET) 880L/min (SPRAY)	35m (JET) 28m (SPRAY)
WRS102-LA-065-NA	With branchpipe					
WRS100-LA-065-HL	With pistol grip					
WRS100-GM-065-NA	Standard	Copper Alloy to BS 1982				
WRS102-GM-065-NA	With branchpipe			Service Controller		
WRS100-GM-065-HL	With pistol grip					



JET/SPRAY NOZZLE WITH CONTROL VALVE

Code No.	Material	Finishing	Inlet Size	Flowrate @ 65Psi (4.4 Bar)	Throwrange @ 65Psi (4.4 Bar)
WRS078-LA-065-NA	Aluminium Alloy	Natural	Male BS Instantaneous	160L/min (JET)	14m (JET & SPRAY)
WRS078-LA-52C-NA	to BS 1490		Storz DIN 52C	44017 : (000 4)	
WRS097-LA-050-NA		Male BS Instantaneous	140L/min (SPRAY)	,	