

## FIRE HYDRANT EQUIPMENT



HYD061-CI-150-RD



HYD055-CI-150-RD

### 3 WAY FIRE HYDRANT

Body material : Cast Iron to BS 1561  
 Outlet : Copper alloy BS 1982  
 Test pressure : 20 bar (300 psi)  
 Working pressure : 15 bar (217 psi)  
 Finishing : Red

Model HYD061-CI-150-RD can be fitted with an underground 6" gate valve with spindle cap (sluice valve) and operated by using a hydrant key and bar (HYD066-CI-030-BK / HYD066-LA-030-NA)

Code No.	Outlet	Inlet
HYD061-CI-150-RD	2 x (2-1/2") Male Thread 1 x 4" Male Thread	6" Table E BS 10 Flange
HYD055-CI-150-RD	2 x 2-1/2" Control Valve with Female BS Instantaneous Outlet 1 x 4" Male Thread	6" Table E BS 10 Flange



### 4 WAY FIRE HYDRANT

Body material : Carbon Steel  
 Outlet : Copper alloy BS 1982  
 Test pressure : 30 bar (435 psi)  
 Working pressure : 20 bar (290 psi)  
 Outlet pressure setting : 7 bar (101 psi)  
 Finishing : Red

Code No.	Outlet	Inlet
HYD052-CS-150-RD	4 x 2-1/2" Pressure Regulating Control Valve with Female BS Instantaneous Outlet	6" ANSI B16.5 Welding Neck Flange 300# FF