

WET AND DRY RISER EQUIPMENT



RATIO TYPE LANDING VALVE TO BS5041

Code No.	Inlet Size	Outlet Size	Flowrate
WRS124-LG-3X1-RD	Male BSP Thread 80mm	BS 336	min
WRS124-LG-2X1-RD		Female	510L/min
WRS124-LG-3X2-RD			

Approved by:

* BRITISH STANDARDS
INSTITUTION APPROVAL



CERTIFIED TO BS 5041 PART 3
LICENCE NO. KM55154



SIRIM
CERTIFIED TO BS 5041-PT.3: 1975
Certification No: P5005705



2-WAY & 4-WAY BREECHING INLET SPECIFICATION

Body	: Ductile Iron / Cast Iron / Copper Alloy
Inlet	: BS Instantaneous Male Copper Alloy to BS 1982
Outlet	: 2 Way Breaching Inlet Flanged 4" table E. BS 10
	: 4 Way Breaching Inlet Flanged 6" table E. BS 10
	: 2 Way Breaching Inlet Flanged 4" table D
	: 2 Way Breaching Inlet Flanged 3" ANSI
Working Pressure	: 10 Bar
Testing Pressure	: 20 Bar

Code No.	Description	Inlet Size	Outlet Size	Body Material
DRS095-DI-BSPN16	2-way breaching inlet	BS 336 Male	Table E/PN 16	Ductile Iron
* WRS115-DI-BSPN16	4-way breaching inlet	BS 336 Male	Table E/PN 16	Ductile Iron
* DRS095-DI-BSPN 16	2-way breaching inlet	BS 336 Male	Table D	Ductile Iron
* DRS095-GM-080AN	2-way breaching inlet	BS 336 Male	3" ANSI	Copper Alloy
DRS095-CI-002-RD	2-way breaching inlet	BS 336 Male	Table E/PN 16	Cast Iron
WRS115-CI-004-RD	4-way breaching inlet	BS 336 Male	Table E/PN 16	Cast Iron

GERMAN BREECHING INLET

Code No.	Description	Outlet Size	Inlet Size
DRS130-GM-STN-NA	2-way breaching inlet	Female BSP Thread 80mm	Storz B75 (89mm)

AIR RELEASE VALVE

Code No.	Inlet Connection
WRS104-GM-020-NA	20mm (3/4") BSP
WRS104-GM-025-NA	25mm (1") BSP



GERMAN LANDING VALVE

Code No.	Inlet Size	Outlet Size
WRS130-GM-90D-NA	Male BSP Thread 50mm	Storz C52 (66mm)
WRS130-LA-90D-NA	Male BSP Thread 50mm	Storz C52 (66mm)

