

Mobile Foam Unit



Water alone may not be sufficient for the fire protection you need. Addition of foam provides better effect on the many types of fires that may occur especially light fuels.

With this mobile foam unit, now you can better utilise the available water supply (eg. Fire hydrant) for better protection.

Water, when mixed with foam, is much lighter and has a larger surface area. This means better coverage and cooling effect. In the case of light fuels, the foam simply covers the fire without sinking into the fuel.

This mobile foam unit is suitable for used in tank farms, oil refineries, airports, aircraft hangers, rubber product plants and even most medium sized factories.

- ◆ One-Man Operation
- ◆ Rechargeable During Use
- ◆ Continuous Operation
- ◆ Light Weight
- ◆ Adjustable Foam Ratio
- ◆ Large Wheel Size
- ◆ Impact Protection

Distributed by

SPECIFICATION

Model	MFU 120
Capacity	120 Litre
Working Pressure	7 Bar
Min. Discharge Time	9 min. @ 7 Bar
Flow Rate	210 litre/min @ 7 bar
Discharge Range	18 m @ 7 bar
Water Supply Hose	65mm X 30m Canvas Hose
Foam Discharge Hose	40mm X 30m Canvas Hose
Full Weight	≈ 185 kg
Overall Height	1070 mm
Overall Width	790 mm
Overall Length	1250 mm
Tank Material	Fibre Glass
Trolley Material	*Mild Steel
Foam Concentrate	**AFFF Foam
Wheel Diameter	16"
Filling Opening	200mm

* Marine Finishing available upon request

** Other Types of Foam Concentrate available upon request

Manufacturer :



EVERSAFE EXTINGUISHER SDN. BHD. 053162-V

Lot 878, Jalan Subang 9, Taman Perindustrian Subang, 47500 Subang Jaya, Selangor D.E., Malaysia
Tel. : +60-3-8024-9898 Fax.: +60-3-8024-7878 e-mail : sales@eversafe.net

In the interest of product improvement, the company reserves the right to amend the specification of the product without prior notice.

Catalog No.:EE-MFU-120-03-01