

EN3 C02 Type Fire Extinguisher

PRESSURE EQUIPMENT DIRECTIVE
APPROVED FIRE EXTINGUISHERS



0029

MARINE EQUIPMENT DIRECTIVE
APPROVED FIRE EXTINGUISHERS



0029

BRITISH STANDARDS INSTITUTION



CERTIFIED TO BS EN3
LICENCE NO. KM 57533



SETSCO




FEX180

FEX182

FEX181

FEX183



- EN3 approved.
- Suitable for Class B & Electrical Hazards.
- High quality and good value.
- Colour coded for instant recognition.
- Available in aluminium and light weight steel.
- Easy to use and leave no messy residue.
- Cylinder Test Pressure: 250 Bar

TECHNICAL SPECIFICATION

	2kg	5kg	2kg	5kg	5kg
EXTINGUISHER TYPE					
MATERIAL	Steel	Steel	Aluminium	Aluminium	Chromium Molybdenum Steel
MODEL NO.	FEX182	FEX183	FEX180	FEX181	FEX177
FIRE RATING	34B	55B	34B	55B	89B
OPERATING TEMPERATURE	-20°C to 60°C	-20°C to 60°C	-20°C to 60°C	-20°C to 60°C	-20°C to 60°C
OPERATING PRESSURE	70 Bar at 20°C	70 Bar at 20°C	70 Bar at 20°C	70 Bar at 20°C	70 Bar at 20°C
CYLINDER SPECIFICATION	97/23/EC	97/23/EC	97/23/EC	97/23/EC	97/23/EC
HEIGHT	625mm	770mm	575mm	695mm	740mm
FULL WEIGHT	8.4kg	15.8kg	6.1kg	12.0kg	14.5kg
EMPTY WEIGHT	6.4kg	10.8kg	4.1kg	7.0kg	9.5kg
DISCHARGE TIME	14 secs	15 secs	14 secs	15 secs	13 secs
RANGE OF THROW (approx)	4 - 5 M	4 - 5 M	4 - 5 M	4 - 5 M	4 - 5 M
CARTON SIZE mm	220 x 180 x 650	230 x 245 x 780	180 x 200 x 530	230 x 240 x 720	230 x 245 x 780

* Pending approval.

The products specified in this brochure are subjected to continuous development and improvement and are subject to alterations without prior notice. All dimensions are in mm unless otherwise specified.