

PORTABLE DRY POWDER FIRE EXTINGUISHER MS1539



Propellant	STORED PRESSURED TYPE (NITROGEN)				
Code No.	FEX132-MS-010-RD	FEX132-MS-020-RD	FEX132-MS-040-RD	FEX132-MS-060-RD	FEX132-MS-090-RD
Capacity, Kg	1.0	2.0	4.0	6.0	9.0
Working Pressure, Bar (Psi)	12 (174)	14 (203)			
Test pressure, Bar (Psi)	25 (362.5)				
Discharge time, sec	6-10	8-12	12-16	21-25	20-28
Overall height, mm	340.0	400.0	475.0		560.0
Cylinder diameter, mm	84.5	109.5	157.0		176.0
Overall weight, Kg	1.9	3.3	7.8	9.3	12.7
Body material	Cold Roll Steel				
Standard	Manufactured and approved to MS1539 Part 1				
Paint finish	Red				
Fire Rating	5A 21B	13A 55B	13A 70B	27A 144B	27A 144B
Carton box size, mm	110x125x345	130165x415	185x205x490		205x205x570
Type of extinguishant	ABC Powder				
Type of fire	A, B, C, E				

PORTABLE CARBON DIOXIDE FIRE EXTINGUISHER MS1539



Selection and installation should be according to MS1539 Part 3.

Inspection and maintenance should be carried out according to MS1539 Part 4.

Body	FEX139-CS-020-RD	FEX139-CS-050-RD
Material	Carbon Steel	
Capacity, kg	2.0	5.0
Working pressure, Bar	60.0 at 27°C	
Overall height, mm	530	770
Overall diameter, mm	113	140
Cylinder test pressure, Bar	250	
Discharge time, sec	18-25	20-30
Standard	Manufactured and approved to MS1539 Part 1	
Full weight, Kg	8.5	18.5
Paint finish	Red	
Fire Rating	21B	55B
Temperature range	-20°C to 60°C	
Discharge range	3 meter	
Carton size	180x195x665	230x230x715
Operating head	Brass	
Type of extinguishant	Carbon Dioxide	
Class of Fire	B,C	